



Applications:

- Automotive
- Security & Surveillance
- Mobile
- Smart Home

Features:

Automatic Controls:

- Automatic Black Level (ABLC)

Image Quality Controls:

- Bad Pixel Correction

Programmable Controls:

- Frame rate and frame size
- Binning Mode
- Manual AEC/AGC/AWB Control
- Two Wire I²C Control with Programmable
- Column and row sub-sampling
- Mirror, flip, windowing and cropping
- Multiple camera frame sync
- Embedded Data Line
- On-chip temperature sensor

Output formats and Interfaces:

- 10-bit raw MIPI CSI-2 2-lane

Other controls:

- Register group access capability

Key Specifications

Optical Format		1/7.5-inch.
Active Pixel Array (1080P)		656H x496V
Pixel Size		3.0 µm x 3.0 µm
Color Filter Array		RGB Bayer Pattern
Chief Ray Angle		29 °
Shutter Type		Global Shutter
Maximum Frame Rate		640 x480 : 240fps
Power Supply	Analog (AVDD)	3.0 – 3.6V (3.3V nominal)
	I/O	1.7 – AVDD
	DVDD	1.2V
Power Consumption	Active	TBD
	Standby	TBD
Output Formats		10-bit RAW
Operating Temperature		-30°C to 85°C
Storage Temperature		-40°C to 95°C
Package Dimensions (µm²)		3,700 x3,460